

Declaration of Performance No

186/1/CPR



Unique identification code of the product-type:	ATLAS GEOFLEX (2019)
Intended use or uses:	Any interior and exterior installation of tiles.
Manufacturer:	ATLAS sp. z o.o. ul. Jana Kilińskiego 2, 91-421 Łódź telefon: +48 (42) 631 89 45 <a href="http://www.atlas.com.pl">www.atlas.com.pl</a>
System or systems of assessment and verification of constancy of performance:	System 3
Harmonized standard:	EN 12004:2007+A1:2012 Notified body No. 0767 MPA Dresden GmbH Notified body No. 1614 Politechnika Lodzka

Declared performance:

Essential characteristics	Performance
Reaction to fire	A1 A1 <sub>n</sub>
Bond strength defined as: <ul style="list-style-type: none"><li>Initial bonding</li></ul>	$\geq 1,0 \text{ N/mm}^2$
Bond durability in conditioning/thermal ageing conditions defined as: <ul style="list-style-type: none"><li>Bonding after thermal ageing</li></ul>	$\geq 1,0 \text{ N/mm}^2$
Bond durability in water/damp conditions defined as: <ul style="list-style-type: none"><li>Bonding after immersion in water</li></ul>	$\geq 1,0 \text{ N/mm}^2$
Bond durability in freeze-thaw cycles conditions defined as: <ul style="list-style-type: none"><li>Bonding after freeze-thaw cycles</li></ul>	$\geq 1,0 \text{ N/mm}^2$
Release/ content of hazardous substances	NPD

The performance of the product is in conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by: Patrycja Stasiak in Łódź, 23.11.2021.

ATLAS sp. z o.o.  
Dyrektor ds. Jakości  
*Stasiak*  
Patrycja Stasiak