

GENIEMAT[®] RST05

SOUND CONTROL UNDERLAYMENT



PRODUCT SPECIFICATION

PRODUCT NAME:	GenieMat RST05
DIMENSION:	Rollgood: 4' wide, 30' long (1.2 m wide, 9.1 m long)
THICKNESS:	3/16" (nom. 5 mm)
DENSITY:	Shall be > 1000 kg/m ³
ROLLS/PALLET:	16

TECHNICAL DATA

REDUCTION OF IMPACT SOUND PRESSURE LEVEL: (ASTM E492/E2179)	GenieMat RST05 tested over 6" concrete slab with 12" x 12" ceramic tile, no ceiling IIC 50 and ΔIIC 20 dB
NATURAL FREQUENCY	Shall not be greater than 70 Hz @ 400 psf loading
HIIC (ASTM WK59631)	Shall be ≥ 62 when tested on an 8" concrete slab with vinyl Shall be ≥ 51 when tested on an 8" concrete slab with tile Shall be ≥ 59 when tested on an 8" concrete slab with engineered wood
POINT LOAD TEST FOR CRACK ISOLATION MEMBRANES: (ANSI 118.12)	Exceeds pass criteria
PUNCTURE TESTING WHEN INSTALLED UNDER LUXURY VINYL TILE: (ASTM F924)	No change when compared to puncture failure limit of luxury vinyl tile tested without underlayment
RESISTANCE TO IMPACT WHEN INSTALLED UNDER LUXURY VINYL TILE: (ASTM F1265)	Luxury vinyl tile shows no signs of breaking or cracking and meets standard criteria
ROLLING LOAD INDENTATION WHEN INSTALLED UNDER LUXURY VINYL TILE: (ASTM F2753)	Luxury vinyl tile shows no signs of indentation and plank separation for 12,500 cycles
TEMPERATURE STABILITY:	-40°F to +240°F (-40°C to +115°C)

For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com

© Pliteq Inc. 2019.

08/19 ^{®/™} Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.com