



<b>Unique identification code of the product-type:</b>	<b>ATLAS WODER DUO EXPRESS (2020)</b>
<b>Intended use or uses:</b>	Any application underneath ceramic tiles, outdoors and in swimming pools.
<b>Manufacturer:</b>	ATLAS sp. z o.o. ul. Jana Kilińskiego 2, 91-421 Lodz, Poland telefon: +48 (42) 631 89 45 <a href="http://www.atlas.com.pl">www.atlas.com.pl</a>
<b>System or systems of assessment and verification of constancy of performance:</b>	System 3
<b>Harmonized standard:</b>	EN 14891:2012 EN 14891:2012/AC:2012 Notified body No. 1301 TECHNICKÝ A SKÚŠOBNÝ ÚSTAV STAVEBNÝ, n.o.

**Declared performance:**

Essential characteristics	Performance
Initial adhesion	$\geq 0,5 \text{ N/mm}^2$
Water tightness	no permeation
Crack bridging ability: • in normal conditions	$\geq 0,75 \text{ mm}$
Durability of initial bonding to climatic impact/ thermal ageing: • adhesion after thermal ageing	$\geq 0,5 \text{ N/mm}^2$
Durability of initial bonding to water/ humidity: • adhesion after immersion in water	$\geq 0,5 \text{ N/mm}^2$
Durability of initial bonding to lime water • adhesion after immersion in lime water	$\geq 0,5 \text{ N/mm}^2$
Durability of initial bonding to freeze/thaw cycles: • adhesion after immersion freeze/thaw cycles	$\geq 0,5 \text{ N/mm}^2$
Release of dangerous substances	NPD

The performance of the product is in conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by: Patrycja Stasiak in Łódź, on 21.01.2022.

ATLAS sp. z o.o.  
Dyrektor ds. Jakości

*Patrycja Stasiak*  
Patrycja Stasiak